

# MTV<sub>25</sub>

Indoor HD Rental LED Display

**LED**igital

Your Local

LED



Application

## LONG LIFESPAN



High quality components, after 1000 hours aging test under 80C, overall light decay rate less than 10%.



## BLACK SMD LED



2121 black SMD LED, increase contrast ratio and enhance the visual performance.



## SUPER WIDE VIEWING ANGLE



Horizontally and vertically  
140 viewing angle, allow  
audience to see the perfect  
image from every direction.

## HIGH PROFILE S-PWM DRIVER IC



Low refresh rate



High refresh rate

The self-refresh circuit is built inside S-PWM, it can significantly  
increase the refresh rate, up to 1920Hz.

## SEAMLESS ALIGNMENT WITH PRECISION




LCD Splicing



LED Splicing

Assemble the display from any direction, size and shape, there will be no gap or black line, only perfect visual effect.

## FAST INSTALLATION



Smart lock design, simple push to connect two cabinet together.

## EASY MAINTENANCE



step 1  
Put the tool to magnet the cabinet



step 2  
Magnet the module, to ensure the tool is in the middle of module



step 3  
Pull the tool gently, Taking off the module



step 4  
Replace a new module in the same way

Front service, get the job done in a few seconds.

## PARAMETERS

Value	MTV25
Pixel pitch	2.5mm
Brightness	700 nits
Pixel configuration	SMD
Colours	281 trillion
Refresh rate	≥ 1920
Pixel matrix per panel	192X192
Pixel matrix per sq.m	160000
Viewing angle ( H/V)	140/140 deg.
Power consumption (max/avg)	650/220 W/sq.m
IP rate	IP40/IP20
Input voltage (AC)	110/240
Panel size(L x W x H)	480X480X80mm
Panel weight(Alu.)	5kgs

# APPLICATIONS

Mall, enterprise, school, stage, bank, police, traffic, custom, hospital, airport, train station, sport arena.



# SYSTEM

